







Home leave operation



Vertical auto swing

## For rooms with no false ceilings nor free floor space

- > Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- > Can easily be installed in both new and refurbishment projects
- > Reduced energy consumption thanks to specially developed DC fan motor
- > The air is comfortably spread up and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- > Maintenance operations can be performed easily from the front of the unit

## FAQ-C + RZQG-L9V1/(8)Y1, RZQSG-L3/9V1/(8)Y1



Indoor unit			FAQ	71C	100C			
Casing	Colour			Fresh White				
Dimensions	Unit HeightxWidthxDepth		mm	290x1,050x238	340x1,200x240			
Sound power level Cooling/Heating			dBA	61/61	65/65			
Sound pressure Cooling High		High/Nom./Low	dBA	45/42/40	49/45/41			
level	Heating	High/Nom./Low	dBA	45/42/40	49/45/41			
Control systems	Infrared rem	ote control		BRC7EB518				
	Wired remote control			BRC1D52 / BRC1E52A/B				

Seasonal Smart

Combination with Seasonal Smart outdoor units ensure high quality, optimal comfort, flexible installation and highest efficiency values.


Seasonal Classic Combination with Seasonal Classic ensures good value for money for all types of commercial

			values.		аррисацонз.					
Efficiency data		FAQ + RZQG/	RZQSG	71C + 71L9V1	100C + 100L9V1	71C + 71L8Y1	100C + 100L8Y1	71C + 71L3V1	100C + 100L9V1	100C + 100L8Y1
Cooling capacity	capacity Nom.		kW	6.8	9.5	6.8	9.5	6.8	9.5	
Heating capacity	Nom.		kW	7.5	10.8	7.5	10.8	7.5	10.8	
Power input	Cooling	Nom.	kW	2.00	2.63	2.00	2.63	2.12	3.16	
	Heating	Nom.	kW	2.03	3.00	2.03	3.00	2.08	3.17	
Seasonal efficiency	Cooling	Energy label		A-	++	A+				
(according to EN14825)		Pdesign	kW	6.80	9.50	6.8	9.5	6.80	9.50	
		SEER		6.51	6.11	6.51	6.11	6.05	5.	61
		Annual energy consumption	kWh	366	545	366	545	393	59	93
	Heating	Energy label		A+				Α	A+	
	(Average	Pdesign	kW	6.33	10.20	6.33	10.2	6.00	6.81	
	climate)	SCOP		4.02	4.01	4.02	4.01	3.90	4.	01
		Annual energy consumption	kWh	2,205	3,562	2,205	3,562	2,155	2,3	78
Nominal efficiency	EER			3.40	3.62	3.40	3.62	3.21	3.	01
	COP			3.70	3.61	3.70	3.61	3.61	3.	41
	Annual energy consumption kWh		kWh	1,000	1,315	1,000	1,315	1,060	1,580	
	Energy label	Cooling/Heating			A	/A	A/A	B/B		

Outdoor unit			RZQG/	RZQSG	71L9V1	100L9V1	71L8Y1	100L8Y1	71L3V1	100L9V1	100L8Y1	
Dimensions	Unit	HeightxWidthxDepth mm		990x940x320	1,430x940x320	990x940x320	1,430x940x320	770x900x320	990x940x320			
Sound power level	Cooling			dBA	64	66	64	66	65	70	69	
Sound pressure	Cooling	Nom.		dBA	48	50	48	50	49/47	53/-		
level	Heating	Nom.		dBA	50	52	50	52	51	57		
	Night quiet mode	Level 1		dBA	43	45	43	45	-	49		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50 -15-				-15~46			
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5				-15~15.5			
Refrigerant	Type/GWP				R-410A/2,087.5							
	Charge		kg/TCO,Eq		2.9/6.1	4.0/8.4	2.9/6.1	4.0/8.4	2.75/5.7	2.9/6.1		
Power supply	Phase/Frequence	ase/Frequency/Voltage Hz/V		1~/50/220-240		3N~/50/380-415		1~/50/2	1~/50/220-240 3N~/			

Contains fluorinated greenhouse gases (1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)





03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP). Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (NFF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



