

# Floor Standing

FXAC60FSBBAR  
16.1 kW



## Features

- Washable filter
- Electrical Defrosting
- Auto Restart
- High efficiency compressor
- High efficiency coil with internal grooved copper tube
- Valve protection
- Low ambient kit
- Auxilliary electrical heating



## Controller

- Auto restart
- 24 hour timer
- Child lock function
- Multi-speed fan



# Floor Standing

## FXAC60FSBBAR



### Technical features

Set	Sizes	FXAC60FSBBAR	
Indoor Unit	Sizes	FXLC60FS-BAR	
Outdoor Unit	Sizes	FXJC60FS-BCR	
Power Input	V/Ph/Hz	380-415/3/50	
Cooling	Capacity	KW	16.11
	Input	W	6700
	Rated current	A	10.5
	EER	W/W	2.41
Heating	Capacity	W	56300+12000
	Input	W	6700+3500
	Rated current	A	10.5+5.3
	COP	W/W	2.46
Max. input consumption	W	12100	
Max. current	A	19.3	
Operation Control		Wireless	
Compressor	Type		Scroll
	Input	W	5750/6750
	Rated current(RLA)	A	9.77/9.84
	Locked rotor Amp(LRA)	A	67
	Thermal protector		Internal
	Capacitor	µF	/
Indoor fan motor	Input	W	349/332/310
	Capacitor	µF	9
	Speed (Hi/Mi/Lo)	rpm	600/550/510
Indoor air flow (Hi/Lo)	m3/h	2180/2000/1850	
External static pressure (Min/Test/Max)	Pa	/	
Indoor noise level (Hi/Lo)	dB(A)	60/57/54	
Outdoor fan motor	Input	W	162+162
	Capacitor	mF	162+162
	Speed	rpm	3.5+3.5
Outdoor noise level	dB(A)	765+765	
Dimension	Indoor (WxHxD)	mm	600x1900x358
	Outdoor (WxHxD)	mm	940x1245x360
Weight	Net/Gross Indoor	kg	65/75
	Net /Gross Outdoor	kg	114/129
Refrigerant	Type		R-410A
	Charge	g	4500
Refrigerant Pipe	Liquid side/ Gas side	mm	12.7/19
	Max.pipe length	m	30
	Max. difference in level	m	15
Operation temperature range	°C	17 to 30	
Ambient temperature range	°C	18-43/-7-24	
Application area	m2	80-134	
Qty'per 20' & 40' & 40HQ	Set	19/38/42	

Nominal cooling capacity based on : - Indoor Air Temp. 27°C DB / 19°C WB - Outdoor Air Temp. 35°C DB  
 Nominal heating capacity based on : - Indoor Air Temp. 21°C DB - Outdoor Air Temp. 7°C DB/6°C WB