

Wall mounted unit

Wall mounted unit for low energy consumption and pleasant comfort

- › Seasonal efficiency values up to A+
- › Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- › The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › 24 hour timer can be set to start heating or cooling anytime during a 24 hour period



Efficiency data			FTXB + RXB	*25C + 25C	*35C + 35C	*50C + 50C	*60C + 60C	
Cooling capacity	Min./Nom./Max.		kW	1.3/2.5/3.0	1.3/3.3/3.8	-/5.48/-	-/6.23/-	
Heating capacity	Min./Nom./Max.		kW	1.3/2.8/4.0	1.3/3.5/4.8	-/5.6/-	-/6.4/-	
Power input	Cooling	Nom.	kW	0.77	0.99	1.71	1.93	
	Heating	Nom.	kW	0.69	0.93	1.49	1.77	
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A+				
		Pdesign	kW	2.50	3.30	5.48	6.23	
		SEER		6.00	6.05	5.93	6.09	
	Heating (Average climate)	Annual energy consumption		kWh	146	191	323	358
		Energy label		A+				
		Pdesign	kW	2.40	2.80	3.64	3.80	
Nominal efficiency	EER	COP	Annual energy consumption	kWh	838	966	1,193	1,310
				kWh	3.25	3.32	3.21	3.23
	Energy label	Cooling	A					
		Heating	A					

Indoor unit			FTXB	*25C	*35C	*50C	*60C
Dimensions	Unit	HeightxWidthxDepth	mm	316x870x310		386x1136x314	
Weight	Unit		kg	8		14	
Fan - Air flow rate	Cooling	High	m ³ /min	9.20	9.30	14.7	16.2
Sound power level	Cooling		dBA	55	58	55	61
	Heating		dBA	55	58	55	61
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control			ARC470A1		AP GS02	

Outdoor unit			RXB	*25C	*35C	*50C	*60C
Dimensions	Unit	HeightxWidthxDepth	mm	616x788x359		793x990x415	
Weight	Unit		kg	27	29	49	
Sound power level	Cooling		dBA	60	62	64	65
	Heating		dBA	60	62	64	65
Operation range	Cooling	Ambient	Min.-Max.	°CDB			
	Heating	Ambient	Min.-Max.	°CWB			
Refrigerant	Type / GWP			R-410A/2,087.5			
Piping connections	Piping length	OU - IU	Max.	m			
	Level difference	IU - OU	Max.	m			
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50 / 220-240			
Current - 50Hz	Maximum fuse amps (MFA)		A	-			

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load